



# Lacq Turbogel

Lacq Turbogel is a powerful cleaning gel for cleaning and refreshing weathered exterior timber. The thixotropic formula makes Turbogel easy to apply on both horizontal and vertical surfaces. The deep cleaning gel penetrates the wood and refreshes the weathered surface.

## Applicable to:

- Decking
- Garden furniture
- Veranda
- Timber cladding
- All kinds of wood

## Preparation:

Remove all dirt & any loose unsound parts from the greyed wood with a broom. Lightly spray & moisten the wood with water. Always test the product on an inconspicuous area first.

## Processing:

1. Stir Lacq turbogel well before use.
2. Apply the gel liberally in the direction of the wood grain with a brush or roller.
3. Let Turbogel work for 20 minutes.
4. Brush the surface with a stiff brush or broom and rinse with water. We recommend it Do not use a high pressure cleaner because the hard jet can damage the wood bring.
5. When the wooden surface has dried completely (at least 48 hours) it is possible cleaned surface after treatment with Lacq Energol, Lacq Hardwoodoil or Lacq Deckingoil.

*Pay attention! Keep out of reach of children. Avoid contact with eyes and skin. Be immediately flush eyes with plenty of water and seek medical advice obtain. Wear suitable protective clothing, gloves and protective equipment the eyes / face. If swallowed, seek medical advice immediately and packaging or label show. Protect metals (e.g. batter) and plants from direct contact (e.g. feed crop and cover ornamental plants with foil).*

*Pay attention! Always put on a sample first to see if you get the desired finish. This can differ per wood type.*

## Coverage:

About 10 m<sup>2</sup> per liter.

*Pay attention! Efficiency always depends on the structure, suction of the wood, the thickness of the layer, the tools used and the conditions of application.*

## Ingredients

Lacq Turbogel contains biodegradable oxalic acid (<10%). Turbogel does not contain solvents, formalhyde, chlorine compounds or amines.

## Available quantities:

1L, 2,5L & 20L.

## Shelf life:

2 years in original unopened packaging, frost-free, in a dry place (temperature between 5 °C and 35 °C). Avoid freezing during transport and storage.

## Safety information:

For detailed safety information, please consult the MSDS. MSDS is available on [www.lacq.eu](http://www.lacq.eu).

The technical information and specifications contained in this data sheet are based on careful investigations and years of practical experience and are provided to the best of our knowledge. The circumstances under which this product works in practice used may cause many variables. This allows VLIEGENTHART B.V. not be held responsible for possible deviations.