



Lacq Parquet Varnish

Lacq Parquet Varnish is an extremely strong no-nonsense lacquer for your hardwood floor and parquet flooring with a very high abrasion resistance based on urethane acrylate die is also suitable for wooden furniture. Parquet Varnish is easy and is extremely suitable for wooden floors that become intensive charge. The Parquet Varnish is a water-based varnish and is odorless. It also results in no overlaps or streaks. The varnish is available in a satin gloss and ultra-matte finish.

Applicable to:

- Floors
- Furniture
- Stairs
- Other interior wood

Processing:

Untreated wood:

1. Degrease the floor with Fluxaf Pro-Clean. Tropical woods, such as Teak, Wengé, etc. degrease with thinner.
2. Sand the surface according to the rules of the wood. Use grain P120 - P150 for this.
3. After sanding, vacuum thoroughly and remove all dust residues.
4. Stir the product well.
5. Product can be applied by roller, brush or paint sprayer.
6. We recommend applying 3 layers for maximum protection.
7. Intermediate sanding with P220 or P320 grit.
8. Always provide ventilation.

Treated wood:

1. First thoroughly remove all old paint, wax or oil layers, as these can cause a negative influence on the adhesion and quality of the Lacq Parquet Varnish, this can be done with the right one sanders and/or cleaning products.
2. Sand the surface according to the rules of the wood. Use grain P120 - P150 for this.
3. After sanding, vacuum thoroughly and remove all dust residues.
4. Stir the product well.
5. Product can be applied by roller or brush.
6. We recommend applying 3 layers for maximum protection.
7. Intermediate sanding with P220 or P240 grit.
8. Always provide ventilation

Pay attention! The product is ready to use, so do not dilute it! Always put on a sample first to see if you get the desired finish. This can differ per wood type.

Coverage:

About 12 m² per liter.

Pay attention! Efficiency always depends on the structure, suction of the wood, the thickness of the layer, the tools used and the conditions of application.

Drying time:

Dust dry:	approx. 1,5 hours.
Recoatable after:	approx. 2 hours.
Min. processingtemperature:	10 °C.
Max. processingtemperature:	30 °C.

Cleaning:

Clean tools with water.

Technical features:

Moisture regulating effect: Neë
Substance: Liquid

Available quantities:

1L & 2,5L.

Available colors:

Invisible (ultra-mat) & Satin.

Shelf life:

2 years in original unopened packaging, frost-free, in a dry place (temperature between 5 °C and 35 °C). Avoid freezing during transport and storage.

Safety information:

For detailed safety information, please consult the MSDS.
MSDS is available on www.lacq.eu.